



ApplianceStor 61MT

Cost Effective Video Viewing and Administration Appliance

Powerful video viewing & administration server. Ideally suited for small and medium installations

Features

Optimized

The AS61MT is optimized for the video surveillance market. It provides the performance and capacity required for the most demanding camera installations.

Easy

It provides effortless installation, management and administration. All administration functions assume technicians with basic to no storage knowledge. Once racked, setup time should be 15 minutes or less.

Open

The AS61MT open platform is designed and optimized to integrate Video Management Software. We prequalified all major OS and VMS providers. We continually add more to ensure the widest possible certification coverage.

SSD Drives

SSD drives are designed to deliver reliable 24x7 operation while also being optimized for low-power consumption. This ensures the best viewing performance.

Powerful

The ApplianceStor 61 Mini Tower Video Viewing Appliance is a cost effective standalone video viewing, monitoring, and administration server. Its small size is ideal for under counter and desktop installations. The AS61MT comes prebuilt and configured, with the OS installed and tested. Most popular VMS can also be preinstalled on request. The AS61MT ships with standard High Definition graphics for video viewing and monitoring capabilities as well as administration and configuration. This eliminates the need, complexity and cost of a separate video viewing and monitoring server.

Simple

The small but powerful AS61MT is packaged in a small enclosure without sacrificing performance. It delivers a big punch as a powerful server, built around the high performance Intel® Skylake dual core i5-6600 3.70GHz processor with multi-threading and 8GB of 2133 MHz DDR4 memory. The AS61MT offers high performance and bandwidth connectivity to meet the requirements of the most demanding

viewing and administration applications. The standard model provides flexible LAN connectivity with two GbE ports and WiFi 802.11a/b/g/n/ac. It ships standard with the Intel 530 HD video graphics. Outputs include dual HDMI and a DVI port supporting up to 4096x2160.

Right Size

The AS61MT is small and powerful complete VMS server solution that is also easy to install and maintain. The AS61MT Video View Appliances come in Mini Tower chassis ideally suited for small security monitoring centers where space savings is critical. Installation and setup is a breeze. The products come standard prebuilt with a complete product test done. Most popular VMS client viewing software can also be preinstalled on request which allows the AS61MT to be up and running in less than 15 minutes after it is unpacked from the box. The AS61MT Video Viewing Appliance is the ultimate viewing center appliance designed specifically for mission-critical video surveillance.

More Features

Integral WiFi & Bluetooth

Integrated support for the latest IEEE 802.11 a/b/g/n/ac Wi-Fi and Bluetooth 4.2. The Bluetooth 4.2 standard includes Smart Ready technology that can now be found on mobile devices such as the on iPhone and Android mobile devices that makes moving critical video to your smart phone or tablet a cinch.

Miracast Wireless Display

Miracast standard provides users with a wireless link between the AS10 and an HDTV and monitor. This eliminates cabling challenges. Miracast is supported in Windows 8.1 and 10.

Performance

Sixth generation Intel® Skylake CPU with significant performance improvements in processing power. It provides a huge increase in video surveillance performance over previous generation processors.

Expandable

It provides an expansion slot for future expansion. The PCI-E slot supports full-height, half-length cards.

For More Information Contact:

Rasilient Systems, Inc.
3281 Kifer Road
Santa Clara, CA 95051
Tel: +1(408) 730-2568
Toll Free +1 (888) 902-8981

General Information:

info@rasilient.com

Sales: Sales@rasilient.com

Technical Support:

techsupport@rasilient.com

Website: www.rasilient.com

Copyright © 2017 Rasilient Systems Inc. Specifications are subject to change without notice. Rasilient and the Rasilient logo are registered trademarks of Rasilient Systems, Inc. PixelStor and PixelStorOS are trademarks or registered trademarks of RASILIENT Systems, Inc. All other names, brands, products, or services are trademarks or registered trademarks of their respective owners.

Specifications

Core Technology	
CPU Type	Intel Skylake i5-6600 3.3 to 3.9GHz
Socket	LGA1151
Core Logic	Intel® H170 Express chipset
Bench Mark/Clock speed	7594/3.30GHz
Memory size	8GB
Memory type	DDR4 2133 DIMM
Expansion	
Expansion Slot :	1
Slot Type:	1 x PCI-E x16 (Gen3 x16 Link)
Storage	
HDD Bays	2 x 3.5"
Drive support	240GB SSD
Removable Storage	1 x Optical DVD-RW
Networking	
Data Ports	2 x GbE
Wireless	WiFi-802.11 a/b/g/n/ac (supporting dual-band 2.4/5GHz), Bluetooth 4.2
Display Outputs	
Onboard graphics	Intel® HD Graphics 530, 1xDVI, 2xHDMI
Onboard graphics performance	985
Optional HD graphic card	HD 7750 1 GB DDR3 mDP, 2xHDMI (DVI & VGA via adapters)
Opt. Graphic Performance	1631
Max Supported Resolution	DVI - 1920x1200 @ 60Hz
	HDMI - 4096x2160 @ 24Hz
	mDP - 4096x2160 @ 60 Hz
I/O Ports	
	2 x USB 2.0 ports (Front)
	4 x USB 3.0 ports (Rear x 4), USB 3.0 Type-C (rear)
	2 x HDMI + 1x DVI ports
	1 x PS/2 keyboard/mouse port
Compliance	
Safety	US/Canada (UL1950-CSA950)
	Europe (CE, EN55022 compliance to EU Directive 89/366/EEC)
EMI	US (FCC, CFR47 Part 15, Class A)
	Europe (CE, EN55022 & EN55024)
	Australia (C-TICK)
	Taiwan (BSMI)
	China (CCC)
Physical Characteristics	
Dimensions (in./mm)	8.7"x 5.1"x 13.5" 220 x 129 x 340
Weight	15lbs./6.8Kg
Power	
Voltage	Single
	115/230V AC
Watts	250
Operating Environment	
Operation temperature	Designed for 24x7x365 Operation
	10°C ~ 35°C
Non operation temperature	-40°C ~ 70°C
Humidity:	20% ~ 90% (Non condensing)
Operating altitude	0 to 10,000'/0 to 3000m