

ApplianceStor 90R

Data Sheet



High-Density VMS Storage Server

The AS90R integrates VMS and storage in a simple to use, high-performance video surveillance storage solution. It is optimized for Video Surveillance applications and delivers the performance required for the most demanding megapixel installations.

Applications

- Medium to large video surveillance locations

Features:

- **1x Intel Xeon E-2134 CPU**
- **Up to 64GB DDR4 DIMM RAM**

Powerful server and storage system, built around the high-performance Intel® Xeon® processor.

Purpose-built open platform to integrate Video Management Software, and Video Analytic Software Providers. All major supported Video Analytic Software providers are prequalified. More are continually added to ensure the widest possible certification coverage.

Effortless installation, management and administration along with advance RAID

Rasilient provides a **complete physical security solution**. All necessary components are offered, including high-performance recording, viewing/monitoring and administration servers, and high-performance storage.



For more information contact:

Tel: +1 (408) 730-2568 | **Toll Free** +1 (888) 902-8981 | **Website:** www.rasilient.com
Sales: sales@rasilient.com | **Technical Support:** techsupport@rasilient.com

Copyright © 2020 Rasilient Systems Inc. Specifications are subject to change without notice.

ApplianceStor 90R

Data Sheet



Specifications

CPU	Intel Xeon E-2134
Memory	Up to 64GB DDR4 RDIMM
Display Output	HD 7750 1 GB DDR3 mDP, 2x HDMI (DVI and VGA via adapters).
Storage	12x 3.5" SATA III HDD in RAID 0, 1, 5, 6, or 10 2x 240, 480, or 960 GB SSD for OS
Networking	4x GbE
Management Port	1x GbE
Input/Output	1x Serial Port, 3x USB 3.0 (2x Rear, 1x Front). 2x USB 2.0, 1x VGA, 1x PS/2 combined keyboard & mouse port
Dimensions (WxHxD)	19" x 3.5" x 25.4" / 483 x 89 x 645 mm
Weight	Max 60 lbs/28 kg
Power	2x 100/240V AC
Watts	800 80PLUS Gold
Operating Temperature	10°C - 35°C



For more information contact:

Tel: +1 (408) 730-2568 | **Toll Free** +1 (888) 902-8981 | **Website:** www.rasiliant.com

Sales: sales@rasiliant.com | **Technical Support:** techsupport@rasiliant.com

Copyright © 2020 Rasiliant Systems Inc. Specifications are subject to change without notice.

Rev 2.3 09/23/2020