

# ApplianceStor90v2





### **Datasheet**

The AS90v2 integrates VMS and storage in a simple to use, high performance video surveillance storage solution. It is optimized for video surveillance applications and delivers the performance required for the most demanding megapixel installations.

**Powerful** storage server, built around the high-performance Intel Xeon processor and 12 direct-attached high-capacity SAS drives (DAS), all in one box.

Purpose-built open platform with MS Windows to integrate Video Management Software (VMS). All major VMS providers are pre-qualified and pre-loaded (e.g., Milestone, Genetec, Digifort, Qognify, ISS, and more). Most are continually added to ensure the widest possible certification coverage.

**Effortless installation,** management and administration.

Rasilient provides a **complete physical security solution**. All necessary components are offered, including high-performance recording, viewing/monitoring and administration servers, and high-performance storage.

### **Features**

- Intel Xeon E-2334 CPU
- Up to 128GB ECC RAM
- 5-yr Warranty

## **Applications**

- All-in-One Storage Server
- Medium to Large Installations

Copyright © 2022 Rasilient Systems, Inc. Specifications are subject to change without notice

#### For more information contact:



# ApplianceStor90v2

Enterprise Grade, 200-Channel Recording Server

## **Specifications**

CPU	Intel Xeon E-2334
GPU	Integrated ASPEED AST2600, Optional Nvidia T400
RAM	Up to 128GB ECC DDR4 2666Mhz
Networking	2x GbE, 1x RJ45 Dedicated Management
Input/Output	4x USB 3.1, 1x USB 3.0, 1x VGA, Optional 2xHDMI, mDP w/ T400
Max Storage	Up to 240TB
SSD	Power-protected, up to 960GB for OS (2x SSD in RAID 1)
Dimensions (W x D x H)	17" x 26.8" x 3.5" / 430 x 680 x 88 mm
Weight	Max 80 lb / 36 kg
Power Supply	1+1 Redundant 800W 100/240V AC 6A 47-63Hz
Operating Temperature	10 - 35 °C
Recording Performance <sup>1</sup>	400 Mbps

<sup>1</sup> Recording performance was testing using Milestone XProtect and RAID5 storage. Performance may be different for other configurations





\* Configuration of product may differ based on options

Copyright © 2022 Rasilient Systems, Inc. Specifications are subject to change without notice

#### For more information contact:

 $\textbf{Tel:} + 1.408.730.2568 \\ \textbf{|Toll Free:} + 1.888.902.8981 \\ \textbf{|Website:} \text{ www.rasilient.com} \\ \textbf{|Sales:} \text{ sales@rasilient.com} \\ \textbf{|Technical Support:} \text{ techsupport@rasilient.com} \\ \textbf{|Technical Support@rasilient.com} \\ \textbf{$